Multi Head Systems Combination Rule

Hisense Air Conditioning | Better Air

AMW2-50U4RJC

Model	Combination of Indoor Units	Cooling Capacity								Heating Capacity								
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER W/W	Total current (A) Rated (Min._Max.)	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP W/W	Total current (A) Rated (Min._Max.)
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
AMW2-50U4RJC*	7	2.10					2.1 (0.8-2.8)	580 (180-1000)	3.6	2.6 (0.8-4.5)	2.50					2.5 (1-3.2)	680 (200-950)	3.7	3 (0.9-4.1)
	9	2.60					2.6 (0.8-3.2)	780 (220-1200)	3.3	3.5 (1-5.4)	3.00					3 (1-4)	860 (220-1250)	3.5	3.7 (1-5.4)
	12	3.50					3.5 (1.2-3.7)	1150 (220-1500)	3.0	5.2 (1-6.8)	3.90					3.9 (1-4.5)	1250 (220-1500)	3.1	5.4 (1-6.5)
	07+07	2.00	2.00				4 (2.1-5.5)	1200 (440-3200)	3.3	5.4 (2-14.5)	2.50	2.50				5 (2-5.6)	1500 (435-3000)	3.3	6.5 (1.9-13)
	07+09	2.00	2.50				4.5 (2.1-5.5)	1200 (460-3100)	3.8	5.4 (2.1-14)	2.50	3.00				5.5 (2-5.95)	1560 (115-3200)	3.5	6.8 (0.5-13.9)
	07+12	1.80	3.20				5 (2.1-5.5)	1200 (460-3100)	4.2	5.4 (2.1-14)	2.30	3.70				6 (2-5.95)	1560 (115-3200)	3.8	6.8 (0.5-13.9)
	07+18	1.40	3.60				5 (2.1-5.5)	1200 (460-3100)	4.2	5.4 (2.1-14)	1.90	4.10				6 (2-5.95)	1560 (115-3200)	3.8	6.8 (0.5-13.9)
	09+09	2.50	2.50				5 (2.1-5.6)	1260 (500-3350)	4.0	5.7 (2.3-15.2)	3.00	3.00				6 (2-6)	1650 (500-3400)	3.6	7.2 (2.2-14.8)
	09+12	2.50	3.10				5.6 (2.1-5.7)	1300 (460-3500)	4.3	5.9 (2.1-15.9)	3.00	3.10				6.1 (2-6.4)	1700 (435-3450)	3.6	7.4 (1.9-15)
	09+18	1.70	3.30				5 (2.1-5.7)	1300 (460-3500)	3.8	5.9 (2.1-15.9)	2.10	3.90				6 (2-6.4)	1700 (435-3450)	3.5	7.4 (1.9-15)
	12+12	2.80	2.80				5.6 (2.1-5.7)	1350 (500-3520)	4.1	6.1 (2.3-15.9)	3.10	3.50				6.6 (2-6.6)	1750 (500-3520)	3.8	7.6 (2.2-15.3)

* A single indoor unit cannot be connected to the multi head outdoor unit as one by one system

AMW3-71U4RJC

Model	Combination of Indoor Units	Cooling Capacity								Heating Capacity								
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER W/W	Total current (A) Rated (Min._Max.)	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP W/W	Total current (A) Rated (Min._Max.)
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
AMW3-71U4RJC*	7	2.10					2.1 (0.8-2.8)	600 (180-1000)	3.5	2.7 (0.8-4.5)	2.50					2.5 (1-3.2)	700 (200-950)	3.6	3 (0.9-4.1)
	9	2.60					2.6 (0.8-3.2)	800 (220-1200)	3.3	3.6 (1-5.4)	3.00					3 (1-4)	900 (220-1250)	3.3	3.9 (1-5.4)
	12	3.50					3.5 (1.2-3.7)	1200 (220-1500)	2.9	5.4 (1-6.8)	3.90					3.9 (1-4.5)	1300 (220-1500)	3.0	5.7 (1-6.5)
	18	5.00					5 (1.6-6)	1600 (450-2200)	3.1	7.2 (2-10)	5.40					5.4 (1.75-6.7)	1800 (400-2200)	3.0	7.8 (1.7-9.6)
	07+07	2.00	2.00				4 (2-5)	1300 (440-2200)	3.1	5.9 (2-10)	5.00					5 (1.75-6.7)	1500 (400-2200)	3.3	6.5 (1.7-9.6)
	07+09	2.00	2.50				4.5 (2-6.5)	1350 (440-2200)	3.3	6.1 (2-10)	2.50	3.00				5.5 (2-8)	1600 (435-3000)	3.4	7 (1.9-13)
	07+12	2.00	3.50				5.5 (2-8)	1600 (460-2550)	3.4	7.2 (2.1-11.5)	2.50	4.00				6.5 (2-9)	1750 (115-3200)	3.7	7.6 (0.5-13.9)
	07+18	2.00	5.00				7 (2-10)	2000 (500-3700)	3.5	9.1 (2.3-16.8)	2.60	5.40				8 (2-10)	2200 (500-3800)	3.6	9.6 (2.2-16.5)
	07+24	1.50	5.50				7 (2-10)	2000 (500-3700)	3.5	9.1 (2.3-16.8)	2.00	6.00				8 (2-10)	2200 (500-3800)	3.6	9.6 (2.2-16.5)
	09+09	2.50	2.50				5 (2-7)	1400 (460-2300)	3.6	6.3 (2.1-10.4)	3.00	3.00				6 (2-9.5)	1700 (435-3700)	3.5	7.4 (1.9-16.1)
	09+12	2.50	3.50				6 (2-8)	1650 (500-3000)	3.6	7.5 (2.3-13.6)	3.30	3.70				7 (2-9.5)	2000 (500-3500)	3.5	8.7 (2.2-15.2)
	09+18	2.50	4.50				7 (2-10)	2000 (500-3800)	3.5	9.1 (2.3-17.2)	2.80	5.20				8 (2-10)	2200 (500-3800)	3.6	9.6 (2.2-16.5)
	09+24	1.82	5.18				7 (2-10)	2000 (500-3800)	3.5	9.1 (2.3-17.2)	2.30	5.70				8 (2-10)	2200 (500-3800)	3.6	9.6 (2.2-16.5)
	12+12	3.50	3.50				7 (2-10)	1980 (500-3750)	3.5	9 (2.3-17)	4.00	4.00				8 (2-9.5)	2200 (500-3900)	3.6	9.6 (2.2-17)
	12+18	2.80	4.20				7 (2-10)	2000 (500-3800)	3.5	8.7 (2.3-17.2)	3.20	4.80				8 (2-10)	2100 (500-3800)	3.8	9.1 (2.2-16.5)
	07+07+07	2.00	2.00	2.00			6 (2-8)	1750 (500-3200)	3.4	7.9 (2.3-14.5)	2.33	2.33	2.33			7 (2-10)	1850 (500-3750)	3.8	8 (2.2-16.3)
	07+07+09	2.00	2.00	2.50			6.5 (2-9)	1850 (500-3500)	3.5	8.4 (2.3-15.9)	2.40	2.40	2.70			7.5 (2-10)	2000 (500-3750)	3.8	8.7 (2.2-16.3)
	07+07+12	2.00	2.00	3.00			7 (2-10)	1900 (500-3700)	3.7	8.6 (2.3-16.8)	2.30	2.30	3.40			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	07+07+18	1.80	1.80	3.40			7 (2-10)	1920 (500-3800)	3.6	8.3 (2.3-17.2)	2.00	2.00	4.00			8 (2-9.7)	2050 (500-3700)	3.9	8.9 (2.2-16.1)
	07+09+09	2.00	2.50	2.50			7 (2-10)	1930 (500-3800)	3.6	8.7 (2.3-17.2)	2.40	2.80	2.80			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	07+09+12	1.70	2.30	3.00			7 (2-10)	1950 (500-3800)	3.6	8.8 (2.3-17.2)	2.20	2.60	3.20			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	07+09+18	1.50	2.00	3.50			7 (2-10)	1960 (500-3800)	3.6	8.9 (2.3-17.2)	1.90	2.30	3.80			8 (2-10)	2050 (500-3730)	3.9	8.9 (2.2-16.2)
	07+12+12	1.60	2.70	2.70			7 (2-10)	1950 (500-3800)	3.6	8 (2.3-17.2)	2.10	2.95	2.95			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	07+12+18*	1.35	2.35	3.30			7 (2-10)	1950 (500-3800)	3.6	8 (2.3-17.2)	1.70	2.70	3.60			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	09+09+09	2.33	2.33	2.33			7 (2-10)	1950 (500-3800)	3.6	8.8 (2.3-17.2)	2.67	2.67	2.67			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	09+09+12	2.10	2.10	2.80			7 (2-10)	1950 (500-3800)	3.6	8 (2.3-17.2)	2.50	2.50	3.00			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	09+09+18	1.80	1.80	3.40			7 (2-10)	1960 (500-3800)	3.6	8 (2.3-17.2)	2.10	2.10	3.80			8 (2-10)	2050 (500-3730)	3.9	8.9 (2.2-16.2)
	09+12+12	2.00	2.50	2.50			7 (2-10)	1950 (500-3800)	3.6	8 (2.3-17.2)	2.20	2.90	2.90			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	09+12+18*	1.59	2.23	3.18			7 (2-10)	1950 (500-3800)	3.6	8 (2.3-17.2)	1.90	2.60	3.50			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	12+12+12	2.33	2.33	2.33			7 (2-10)	1950 (500-3800)	3.6	8 (2.3-17.2)	2.67	2.67	2.67			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)
	12+12+18*	2.00	2.00	3.00			7 (2-10)	1950 (500-3800)	3.6	8 (2.3-17.2)	2.30	2.30	3.40			8 (2-10)	2060 (500-3750)	3.9	9 (2.2-16.3)

* 07+12+18 and 09+12+18 and 12+12+18 can match three high wall units only; A single indoor unit cannot be connected to the multi head outdoor unit as one by one system.

Hisense Air Conditioning | Better Air

AMW4-80U4RJC

Model	Combination of Indoor Units	Cooling Capacity								Heating Capacity							
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER	Total current (A) Rated (Min._Max.)	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP	Total current (A) Rated (Min._Max.)
		Room A	Room B	Room C	Room D	Room E			W/W		Room A	Room B	Room C	Room D	Room E			W/W	
AMW4-80U4RJC*	7	2.10					2.1 (0.8-2.8)	600 (180-1000)	3.5	2.7 (0.8-4.5)	2.50					2.5 (1-3.2)	700 (200-950)	3.6	3 (0.9-4.1)
	9	2.60					2.6 (0.8-3.2)	800 (220-1200)	3.3	3.6 (1-5.4)	3.00					3 (1-4)	900 (220-1250)	3.3	3.9 (1-5.4)
	12	3.50					3.5 (1.2-3.7)	1200 (220-1500)	2.9	5.4 (1-6.8)	3.90					3.9 (1-4.5)	1300 (220-1500)	3.0	5.7 (1-6.5)
	18	5.00					5 (1.6-6)	1600 (450-2200)	3.1	7.2 (2-10)	5.40					5.4 (1.75-6.7)	1800 (400-2200)	3.0	7.8 (1.7-9.6)
	24	7.00					7 (2.2-7.9)	2500 (450-3200)	2.8	10.9 (2-14.5)	7.50					7.5 (2.1-8)	2700 (450-3600)	2.8	11.7 (2-15.7)
	07+07	2.00	2.00				4 (2-5)	1300 (440-2200)	3.1	5.9 (2-10)	5.00					5 (1.75-6.7)	1500 (400-2200)	3.3	6.5 (1.7-9.6)
	07+09	2.00	2.50				4.5 (2-6.5)	1350 (440-2200)	3.3	6.1 (2-10)	2.50	3.00				5.5 (2-8)	1600 (435-3000)	3.4	7 (1.9-13)
	07+12	2.00	3.50				5.5 (2-8)	1600 (460-2550)	3.4	7.2 (2.1-11.5)	2.50	4.00				6.5 (2-9)	1750 (115-3200)	3.7	7.6 (0.5-13.9)
	07+18	2.10	5.00				7.1 (2.4-8)	2100 (500-3300)	3.4	9.1 (2.3-14.9)	2.60	5.50				8.1 (2-8.5)	2300 (400-3400)	3.5	10 (1.7-14.8)
	07+24	1.80	6.20				8 (2.4-8)	2100 (500-3300)	3.8	9.1 (2.3-14.9)	2.00	7.00				9 (2-8.5)	2300 (400-3400)	3.9	10 (1.7-14.8)
	09+09	2.50	2.50				5 (2-7)	1400 (460-2300)	3.6	6.3 (2.1-10.4)	3.00	3.00				6 (2-9.5)	1700 (435-3700)	3.5	7.4 (1.9-16.1)
	09+12	2.50	3.50				6 (2-8)	1650 (500-3000)	3.6	7.5 (2.3-13.6)	3.30	3.70				7 (2-9.5)	2000 (500-3500)	3.5	8.7 (2.2-15.2)
	09+18	2.60	5.00				7.6 (2.4-9)	2200 (500-3500)	3.5	9.6 (2.3-15.9)	3.00	5.40				8.4 (2-9.5)	2350 (400-3600)	3.6	10.2 (1.7-15.7)
	09+24	2.10	5.90				8 (2.4-9)	2200 (500-3500)	3.6	9.6 (2.3-15.9)	2.60	6.40				9 (2-9.5)	2350 (400-3600)	3.8	10.2 (1.7-15.7)
	12+12	3.50	3.50				7 (2.2-8)	2150 (500-3200)	3.3	9.3 (2.3-14.5)	3.80	3.80				7.6 (1.8-9)	2400 (400-3500)	3.2	10.4 (1.7-15.2)
	12+18	3.00	5.00				8 (2.2-9.5)	2400 (500-3500)	3.3	10.4 (2.3-15.9)	3.50	5.50				9 (1.8-9.7)	2500 (400-3600)	3.6	10.9 (1.7-15.7)
	12+24	2.66	5.34				8 (2.2-9.5)	2400 (500-3500)	3.3	10.4 (2.3-15.9)	3.10	5.90				9 (1.8-9.7)	2500 (400-3600)	3.6	10.9 (1.7-15.7)
	18+18	4.00	4.00				8 (2.2-9.5)	2400 (500-3500)	3.3	10.4 (2.3-15.9)	4.50	4.50				9 (1.8-9.7)	2500 (400-3600)	3.6	10.9 (1.7-15.7)
	07+07+07	2.00	2.00	2.00			6 (2-8)	1750 (500-3200)	3.4	7.9 (2.3-14.5)	2.33	2.33	2.33			7 (2-10)	1850 (500-3750)	3.8	8 (2.2-16.3)
	07+07+09	2.10	2.10	2.60			6.8 (2.4-8.7)	1980 (540-3500)	3.4	8.6 (2.4-15.9)	2.60	2.60	3.00			8.2 (2.2-9.2)	2200 (420-3500)	3.7	9.6 (1.8-15.2)
	07+07+12	2.10	2.10	3.50			7.7 (2.4-9)	2200 (540-3500)	3.5	9.6 (2.4-15.9)	2.60	2.60	3.50			8.7 (2.2-9.5)	2400 (420-3700)	3.6	10.4 (1.8-16.1)
	07+07+18	1.80	1.80	4.40			8 (2.4-10)	2250 (540-3600)	3.6	9.8 (2.4-16.3)	2.30	2.30	4.40			9 (2.2-10.5)	2350 (420-3800)	3.8	10.2 (1.8-16.5)
	07+07+24	1.45	1.45	5.10			8 (2.4-10)	2250 (540-3600)	3.6	9.8 (2.4-16.3)	1.80	1.80	5.40			9 (2.2-10.5)	2350 (420-3800)	3.8	10.2 (1.8-16.5)
	07+09+09	2.10	2.60	2.60			7.3 (2.4-9.2)	2100 (540-3600)	3.5	9.1 (2.4-16.3)	2.60	3.00	3.00			8.6 (2.2-9.5)	2350 (420-3800)	3.7	10.2 (1.8-16.5)
	07+09+12	2.00	2.50	3.50			8 (2.4-9.5)	2300 (540-3700)	3.5	10 (2.4-16.8)	2.50	3.00	3.50			9 (2.2-10)	2400 (420-3800)	3.8	10.4 (1.8-16.5)
	07+09+18	1.70	2.10	4.20			8 (2.4-11)	2200 (540-3750)	3.6	9.6 (2.4-17)	2.20	2.40	4.40			9 (2.2-10.5)	2350 (420-3800)	3.8	10.2 (1.8-16.5)
	07+09+24	1.40	1.75	4.85			8 (2.4-11)	2200 (540-3750)	3.6	9.6 (2.4-17)	1.70	2.10	5.20			9 (2.2-10.5)	2350 (420-3800)	3.8	10.2 (1.8-16.5)
	07+12+12	2.00	3.00	3.00			8 (2.4-10)	2250 (540-3750)	3.6	9.8 (2.4-17)	2.40	3.30	3.30			9 (2.2-10)	2400 (420-3900)	3.8	10.4 (1.8-17)
	07+12+18	1.50	2.70	3.80			8 (2.4-10)	2250 (540-3750)	3.6	9.8 (2.4-17)	1.90	3.00	4.10			9 (2.2-10)	2400 (420-3900)	3.8	10.4 (1.8-17)
	07+12+24*	1.30	2.20	4.50			8 (2.4-10)	2250 (540-3750)	3.6	9.8 (2.4-17)	1.60	2.50	4.90			9 (2.2-10)	2400 (420-3900)	3.8	10.4 (1.8-17)
	09+09+09*	2.67	2.67	2.67			8 (2.4-10)	2230 (540-3800)	3.6	9.7 (2.4-17.2)	3.00	3.00	3.00			9 (2.2-10)	2400 (420-3900)	3.8	10.4 (1.8-17)
	09+09+12	2.50	2.50	3.00			8 (2.4-10)	2230 (540-3850)	3.6	9.7 (2.4-17.4)	2.80	2.80	3.40			9 (2.2-10)	2350 (420-3900)	3.8	10.2 (1.8-17)
	09+09+18	2.10	2.10	3.80			8 (2.4-10.5)	2230 (540-3850)	3.6	9.7 (2.4-17.4)	2.60	2.60	3.80			9 (2.2-11)	2300 (420-3850)	3.9	10 (1.8-16.7)
	09+09+24	1.70	1.70	4.60			8 (2.4-10.5)	2230 (540-3850)	3.6	9.7 (2.4-17.4)	2.00	2.00	5.00			9 (2.2-11)	2300 (420-3850)	3.9	10 (1.8-16.7)
	09+12+12	2.00	3.00	3.00			8 (2.4-10.5)	2230 (540-3850)	3.6	9.7 (2.4-17.4)	2.40	3.30	3.30			9 (2.2-10)	2350 (420-3900)	3.8	10.2 (1.8-17)
	09+12+18	2.20	2.50	3.30			8 (2.4-11.5)	2230 (540-3850)	3.6	9.7 (2.4-17.4)	2.40	2.90	3.70			9 (2.2-10.5)	2300 (420-3850)	3.9	10 (1.8-16.7)
	09+12+24*	1.50	2.10	4.40			8 (2.4-11.5)	2230 (540-3850)	3.6	9.7 (2.4-17.4)	1.90	2.50	4.60			9 (2.2-10.5)	2300 (420-3850)	3.9	10 (1.8-16.7)
	12+12+12	2.67	2.67	2.67			8 (2.4-10.5)	2230 (540-3850)	3.6	9.7 (2.4-17.4)	3.00	3.00	3.00			9 (2.2-10.5)	2400 (420-3900)	3.8	10.4 (1.8-17)
	07+07+07+07	2.00	2.00	2.00	2.00		8 (2.6-10)	2200 (580-3700)	3.6	9.6 (2.6-16.8)	2.25	2.25	2.25	2.25		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+07+09	1.90	1.90	1.90	2.30		8 (2.6-10)	2200 (580-3750)	3.6	9.6 (2.6-17)	2.20	2.20	2.20	2.40		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+07+12	1.85	1.85	1.85	2.45		8 (2.6-10)	2200 (580-3800)	3.6	9.6 (2.6-17.2)	2.10	2.10	2.10	2.70		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+07+18	1.50	1.50	1.50	3.50		8 (2.6-10)	2220 (580-3850)	3.6	9.7 (2.6-17.4)	1.90	1.90	1.90	3.30		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+09+09	1.80	1.80	2.20	2.20		8 (2.6-10)	2200 (580-3800)	3.6	9.6 (2.6-17.2)	2.00	2.00	2.50	2.50		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+09+12	1.80	1.80	2.00	2.40		8 (2.6-10)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	1.90	1.90	2.50	2.70		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+09+18*	1.40	1.40	1.70	3.50		8 (2.6-10)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	1.90	1.90	1.90	3.30		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+12+12	1.75	1.75	2.25	2.25		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	1.90	1.90	2.60	2.60		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+07+12+18*	1.28	1.28	2.24	3.20		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	1.70	1.70	2.50	3.10		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+09+09+09	1.70	2.10	2.10	2.10		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	2.10	2.30	2.30	2.30		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+09+09+12	1.70	2.05	2.05	2.20		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	1.90	2.30	2.30	2.50		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+09+09+18*	1.33	1.66	1.66	3.35		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	1.80	1.90	1.90	3.40		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	07+09+12+12	1.60	2.00	2.20	2.20		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	2.00	2.20	2.40	2.40		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	09+09+09+09	2.00	2.00	2.00	2.00		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	2.25	2.25	2.25	2.25		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)
	09+09+09+12	1.90	1.90	1.90	2.30		8 (2.6-10.5)	2200 (580-3850)	3.6	9.6 (2.6-17.4)	2.10	2.10	2.10	2.70		9 (2.2-11)	2350 (460-3700)	3.8	10.2 (2-16.1)

* 7+12+24 and 9+12+24 can match three high wall units only; 07+07+09+18 and 07+07+12+18 and 07+09+09+18 can match four high wall units only; A single indoor unit cannot be connected to the multi head outdoor unit as one by one system

Hisense Air Conditioning | Better Air

AMW4-100U4RQA

Model	Combination of Indoor Units	Cooling Capacity								Heating Capacity							
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER W/W	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP W/W
		Room A	Room B	Room C	Room D	Room E				Room A	Room B	Room C	Room D	Room E			
AMW4-100U4RQA*	7	2.10					2.1 (0.8-2.2)	600 (500-800)	3.50	2.10					2.1 (1-2.27)	530 (450-740)	3.96
	9	2.60					2.6 (0.8-2.72)	740 (500-1000)	3.51	2.60					2.6 (1-2.81)	650 (450-920)	4.00
	12	3.50					3.5 (1.2-3.67)	990 (500-1340)	3.54	3.50					3.5 (1-3.78)	870 (450-1230)	4.02
	18	5.00					5 (1.6-5.24)	1410 (500-1910)	3.55	5.00					5 (1.75-5.41)	1240 (450-1760)	4.03
	24	7.00					7 (2.2-7.33)	2000 (500-2670)	3.50	7.00					7 (2.1-7.57)	1740 (450-2460)	4.02
	07+12	2.10	3.50				5.6 (2-5.87)	1580 (540-2140)	3.54	2.10	3.50				5.6 (2-6.05)	1390 (460-1970)	4.03
	07+18	2.10	5.00				7.1 (2.4-7.44)	2000 (540-2710)	3.55	2.10	5.00				7.1 (2-7.68)	1760 (500-2500)	4.03
	07+24	2.10	7.00				9.1 (2.4-9.53)	2560 (540-3470)	3.55	2.10	7.00				9.1 (2-9.84)	2260 (500-3200)	4.03
	09+12	2.60	3.50				6.1 (2-6.39)	1720 (540-2330)	3.55	2.60	3.50				6.1 (2-6.6)	1520 (500-2150)	4.01
	09+18	2.60	5.00				7.6 (2.4-7.96)	2140 (540-2900)	3.55	2.60	5.00				7.6 (2-8.22)	1890 (500-2680)	4.02
	09+24	2.60	7.00				9.6 (2.2-10.06)	2700 (540-3660)	3.56	2.60	7.00				9.6 (1.8-10.38)	2380 (500-3380)	4.03
	12+12	3.50	3.50				7 (2.2-7.33)	1970 (540-2670)	3.55	3.50	3.50				7 (1.8-7.57)	1740 (500-2460)	4.02
	12+18	3.50	5.00				8.5 (2.2-8.91)	2390 (540-3240)	3.56	3.50	5.00				8.5 (1.8-9.19)	2110 (500-2990)	4.03
	12+24	3.50	7.00				10.5 (2.2-11)	2950 (540-4000)	3.56	3.50	7.00				10.5 (1.8-11.35)	2610 (500-3690)	4.02
	18+18	5.00	5.00				10 (2.2-10.48)	2810 (540-3810)	3.56	5.00	5.00				10 (1.8-10.81)	2480 (500-3520)	4.03
	18+24	4.38	6.13				10.5 (2.2-11)	2950 (540-4000)	3.56	4.63	6.48				11.1 (1.8-12)	2750 (500-3900)	4.04
	24+24	5.25	5.25				10.5 (2.2-11)	2950 (540-4000)	3.56	5.55	5.55				11.1 (1.8-12)	2750 (500-3900)	4.04
	07+07+07	2.10	2.10	2.10			6.3 (2-6.6)	1770 (560-2400)	3.56	2.10	2.10	2.10			6.3 (2-6.81)	1570 (500-2220)	4.01
	07+07+09	2.10	2.10	2.60			6.8 (2.4-7.12)	1920 (560-2600)	3.54	2.10	2.10	2.60			6.8 (2.2-7.35)	1690 (520-2390)	4.02
	07+07+18	2.10	2.10	5.00			9.2 (2.4-9.64)	2590 (560-3510)	3.55	2.10	2.10	5.00			9.2 (2.2-9.95)	2280 (520-3240)	4.04
	07+07+24	1.97	1.97	6.56			10.5 (2.4-11)	2950 (560-4000)	3.56	2.08	2.08	6.94			11 (2.2-11.89)	2750 (520-3870)	4.00
	07+09+12	2.10	2.60	3.50			8.2 (2.4-8.59)	2310 (560-3130)	3.55	2.10	2.60	3.50			8.2 (2.2-8.87)	2040 (520-2890)	4.02
	07+09+18	2.10	2.60	5.00			9.7 (2.4-10.16)	2730 (560-3700)	3.55	2.10	2.60	5.00			9.7 (2.2-10.49)	2410 (520-3410)	4.02
	07+09+24	1.89	2.33	6.28			10.5 (2.4-11)	2950 (560-4000)	3.56	1.99	2.47	6.64			11 (2.2-11.89)	2750 (520-3870)	4.00
	07+12+12	2.10	3.50	3.50			9.1 (2.4-9.53)	2560 (560-3470)	3.55	2.10	3.50	3.50			9.1 (2.2-9.84)	2260 (520-3200)	4.03
	07+12+18	2.08	3.47	4.95			10.5 (2.4-11)	2950 (560-4000)	3.56	2.10	3.50	5.00			10.6 (2.2-11.46)	2630 (520-3730)	4.03
	07+12+24	1.75	2.92	5.83			10.5 (2.4-11)	2950 (560-4000)	3.56	1.85	3.08	6.17			11.1 (2.2-12)	2750 (520-3900)	4.04
	07+18+18	1.82	4.34	4.34			10.5 (2.4-11)	2950 (560-4000)	3.56	1.93	4.59	4.59			11.1 (2.2-12)	2750 (520-3900)	4.04
	09+09+12	2.60	2.60	3.50			8.7 (2.4-9.11)	2450 (560-3320)	3.55	2.60	2.60	3.50			8.7 (2.2-9.41)	2160 (520-3060)	4.03
	09+09+18	2.60	2.60	5.00			10.2 (2.4-10.69)	2870 (560-3890)	3.55	2.60	2.60	5.00			10.2 (2.2-11.03)	2530 (520-3590)	4.03
	09+09+24	2.24	2.24	6.03			10.5 (2.4-11)	2950 (560-4000)	3.56	2.37	2.37	6.37			11 (2.2-11.89)	2750 (520-3870)	4.00
	09+12+12	2.60	3.50	3.50			9.6 (2.4-10.06)	2700 (560-3660)	3.56	2.60	3.50	3.50			9.6 (2.2-10.38)	2380 (520-3380)	4.03
	09+12+18	2.46	3.31	4.73			10.5 (2.4-11)	2950 (560-4000)	3.56	2.60	3.50	5.00			11.1 (2.2-12)	2750 (520-3900)	4.04
	09+12+24	2.08	2.81	5.61			10.5 (2.4-11)	2950 (560-4000)	3.56	2.20	2.97	5.93			11.1 (2.2-12)	2750 (520-3900)	4.04
	09+18+18	2.17	4.17	4.17			10.5 (2.4-11)	2950 (560-4000)	3.56	2.29	4.41	4.41			11.1 (2.2-12)	2750 (520-3900)	4.04
	09+18+24	1.87	3.60	5.03			10.5 (2.4-11)	2950 (560-4000)	3.56	1.98	3.80	5.32			11.1 (2.2-12)	2750 (520-3900)	4.04
	12+12+12	3.50	3.50	3.50			10.5 (2.4-11)	2950 (560-4000)	3.56	3.50	3.50	3.50			10.5 (2.2-11.35)	2610 (520-3690)	4.02
	12+12+18	3.06	3.06	4.38			10.5 (2.4-11)	2950 (560-4000)	3.56	3.24	3.24	4.63			11.1 (2.2-12)	2750 (520-3900)	4.04
	12+12+24	2.63	2.63	5.25			10.5 (2.4-11)	2950 (560-4000)	3.56	2.78	2.78	5.55			11.1 (2.2-12)	2750 (520-3900)	4.04
	12+18+18	2.72	3.89	3.89			10.5 (2.4-11)	2950 (560-4000)	3.56	2.88	4.11	4.11			11.1 (2.2-12)	2750 (520-3900)	4.04
	07+07+07+07	2.10	2.10	2.10	2.10		8.4 (2.6-8.8)	2360 (580-3200)	3.56	2.10	2.10	2.10	2.10		8.4 (2.2-9.08)	2090 (560-2960)	4.02
	07+07+07+09	2.10	2.10	2.10	2.60		8.9 (2.6-9.32)	2510 (580-3400)	3.55	2.10	2.10	2.10	2.60		8.9 (2.2-9.62)	2210 (560-3130)	4.03
	07+07+07+12	2.10	2.10	2.10	3.50		9.8 (2.6-10.27)	2760 (580-3740)	3.55	2.10	2.10	2.10	3.50		9.8 (2.2-10.6)	2430 (560-3450)	4.03
	07+07+07+18	1.95	1.95	1.95	4.65		10.5 (2.6-11)	2950 (580-4000)	3.56	2.06	2.06	2.06	4.91		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+07+07+24	1.66	1.66	1.66	5.53		10.5 (2.6-11)	2950 (580-4000)	3.56	1.75	1.75	1.75	5.84		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+07+09+09	2.10	2.10	2.60	2.60		9.4 (2.6-9.85)	2650 (580-3590)	3.55	2.10	2.10	2.60	2.60		9.4 (2.2-10.16)	2330 (560-3310)	4.03
	07+07+09+12	2.10	2.10	2.60	3.50		10.3 (2.6-10.79)	2900 (580-3930)	3.55	2.10	2.10	2.60	3.50		10.3 (2.2-11.14)	2560 (560-3620)	4.02
	07+07+09+18	1.87	1.87	2.31	4.45		10.5 (2.6-11)	2950 (580-4000)	3.56	1.98	1.98	2.45	4.70		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+07+09+24	1.60	1.60	1.98	5.33		10.5 (2.6-11)	2950 (580-4000)	3.56	1.69	1.69	2.09	5.63		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+07+12+12	1.97	1.97	3.28	3.28		10.5 (2.6-11)	2950 (580-4000)	3.56	2.08	2.08	3.47	3.47		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+07+12+18	1.74	1.74	2.89	4.13		10.5 (2.6-11)	2950 (580-4000)	3.56	1.84	1.84	3.06	4.37		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+07+12+24	1.50	1.50	2.50	5.00		10.5 (2.6-11)	2950 (580-4000)	3.56	1.59	1.59	2.64	5.29		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+09+09+09	2.10	2.60	2.60	2.60		9.9 (2.6-10.37)	2790 (580-3780)	3.55	2.10	2.60	2.60	2.60		9.9 (2.2-10.7)	2460 (560-3480)	4.02
	07+09+09+12	2.04	2.53	2.53	3.40		10.5 (2.6-11)	2950 (580-4000)	3.56	2.10	2.60	2.60	3.50		10.8 (2.2-11.68)	2680 (560-3800)	4.03
	07+09+09+18	1.79	2.22	2.22	4.27		10.5 (2.6-11)	2950 (580-4000)	3.56	1.90	2.35	2.35	4.51		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+09+09+24	1.54	1.91	1.91	5.14		10.5 (2.6-11)	2950 (580-4000)	3.56	1.63	2.02	2.02	5.43		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+09+12+12	1.89	2.33	3.14	3.14		10.5 (2.6-11)	2950 (580-4000)	3.56	1.99	2.47	3.32	3.32		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+09+12+18	1.67	2.07	2.78	3.98		10.5 (2.6-11)	2950 (580-4000)	3.56	1.77	2.19	2.94	4.21		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+09+12+24	1.45	1.80	2.42	4.84		10.5 (2.6-11)	2950 (580-4000)	3.56	1.53	1.90	2.56	5.11		11.1 (2.2-12)	2750 (560-3900)	4.04
	07+12+12+12	1.75	2.92	2.92	2.92		10.5 (2.6-11)	2950 (580-4000)	3.56	1.85	3.08	3.08	3.08		11.1 (2.2-12)	2750 (560-3900)	4.04

Model	Combination of Indoor Units	Heating Capacity								
		Capacity of each indoor unit (kW)					Total current (A) Rated (Min._Max.)			
		Room A	Room B	Room C	Room D	Room E				
AMW4-100U4RQA*	7	2.10					2.3 (2-3.2)			
	9	2.60					2.8 (2-4)			
	12	3.50					3.8 (2-5.3)			
	18	5.00					5.4 (2-7.7)			
	24	7.00					7.6 (2-10.7)			
	07+12	2.10	3.50				6 (2-8.6)			
	07+18	2.10	5.00				7.7 (2.2-10.9)			
	07+24	2.10	7.00				9.8 (2.2-13.9)			
	09+12	2.60	3.50				6.6 (2.2-9.3)			
	09+18	2.60	5.00				8.2 (2.2-11.7)			
	09+24	2.60	7.00				10.3 (2.2-14.7)			
	12+12	3.50	3.50				7.6 (2.2-10.7)			
	12+18	3.50	5.00				9.2 (2.2-13)			
	12+24	3.50	7.00				11.3 (2.2-16)			
	18+18	5.00	5.00				10.8 (2.2-15.3)			
	18+24	4.63	6.48				12 (2.2-17)			
	24+24	5.55	5.55				12 (2.2-17)			
	07+07+07	2.10	2.10	2.10			6.8 (2.2-9.7)			
	07+07+09	2.10	2.10	2.60			7.3 (2.3-10.4)			
	07+07+18	2.10	2.10	5.00			9.9 (2.3-14.1)			
	07+07+24	2.08	2.08	6.94			12 (2.3-16.8)			
	07+09+12	2.10	2.60	3.50			8.9 (2.3-12.6)			
	07+09+18	2.10	2.60	5.00			10.5 (2.3-14.8)			
	07+09+24	1.99	2.47	6.64			12 (2.3-16.8)			
	07+12+12	2.10	3.50	3.50			9.8 (2.3-13.9)			
	07+12+18	2.10	3.50	5.00			11.4 (2.3-16.2)			
	07+12+24	1.85	3.08	6.17			12 (2.3-17)			
	07+18+18	1.93	4.59	4.59			12 (2.3-17)			
	09+09+12	2.60	2.60	3.50			9.4 (2.3-13.3)			
	09+09+18	2.60	2.60	5.00			11 (2.3-15.6)			
	09+09+24	2.37	2.37	6.37			12 (2.3-16.8)			
	09+12+12	2.60	3.50	3.50			10.3 (2.3-14.7)			
	09+12+18	2.60	3.50	5.00			12 (2.3-17)			
	09+12+24	2.20	2.97	5.93			12 (2.3-17)			
	09+18+18	2.29	4.41	4.41			12 (2.3-17)			
	09+18+24	1.98	3.80	5.32			12 (2.3-17)			
	12+12+12	3.50	3.50	3.50			11.3 (2.3-16)			
	12+12+18	3.24	3.24	4.63			12 (2.3-17)			
	12+12+24	2.78	2.78	5.55			12 (2.3-17)			
	12+18+18	2.88	4.11	4.11			12 (2.3-17)			
	07+07+07+07	2.10	2.10	2.10	2.10		9.1 (2.4-12.9)			
	07+07+07+09	2.10	2.10	2.10	2.60		9.6 (2.4-13.6)			
	07+07+07+12	2.10	2.10	2.10	3.50		10.6 (2.4-15)			
	07+07+07+18	2.06	2.06	2.06	4.91		12 (2.4-17)			
	07+07+07+24	1.75	1.75	1.75	5.84		12 (2.4-17)			
	07+07+09+09	2.10	2.10	2.60	2.60		10.1 (2.4-14.4)			
	07+07+09+12	2.10	2.10	2.60	3.50		11.1 (2.4-15.7)			
	07+07+09+18	1.98	1.98	2.45	4.70		12 (2.4-17)			
	07+07+09+24	1.69	1.69	2.09	5.63		12 (2.4-17)			
	07+07+12+12	2.08	2.08	3.47	3.47		12 (2.4-17)			
	07+07+12+18	1.84	1.84	3.06	4.37		12 (2.4-17)			
	07+07+12+24	1.59	1.59	2.64	5.29		12 (2.4-17)			
	07+09+09+09	2.10	2.60	2.60	2.60		10.7 (2.4-15.1)			
	07+09+09+12	2.10	2.60	2.60	3.50		11.7 (2.4-16.5)			
	07+09+09+18	1.90	2.35	2.35	4.51		12 (2.4-17)			
	07+09+09+24	1.63	2.02	2.02	5.43		12 (2.4-17)			
	07+09+12+12	1.99	2.47	3.32	3.32		12 (2.4-17)			
	07+09+12+18	1.77	2.19	2.94	4.21		12 (2.4-17)			
	07+09+12+24	1.53	1.90	2.56	5.11		12 (2.4-17)			
	07+12+12+12	1.85	3.08	3.08	3.08		12 (2.4-17)			

Hisense Air Conditioning | Better Air

AMW4-100U4RQA

Model	Combination of Indoor Units	Cooling Capacity								Heating Capacity							
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER W/W	Total current (A) Rated (Min._Max.)	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP W/W	Total current (A) Rated (Min._Max.)
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
AMW4-100U4RQA*	07+12+12+18	1.56	2.61	2.61	3.72		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	1.65	2.76	2.76	3.94		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+09+09+09	2.60	2.60	2.60	2.60		10.4 (2.6-10.9)	2930 (580-3970)	3.55	12.8 (2.5-17.3)	2.60	2.60	2.60	2.60		10.4 (2.2-11.24)	2580 (560-3660)	4.03	11.2 (2.4-15.9)
	09+09+09+12	2.42	2.42	2.42	3.25		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	2.55	2.55	2.55	3.44		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+09+09+18	2.13	2.13	2.13	4.10		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	2.26	2.26	2.26	4.34		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+09+09+24	1.85	1.85	1.85	4.97		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	1.95	1.95	1.95	5.25		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+09+12+12	2.24	2.24	3.01	3.01		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	2.37	2.37	3.18	3.18		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+09+12+18	1.99	1.99	2.68	3.83		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	2.11	2.11	2.84	4.05		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+09+12+24	1.74	1.74	2.34	4.68		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	1.84	1.84	2.48	4.95		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+12+12+12	2.08	2.81	2.81	2.81		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	2.20	2.97	2.97	2.97		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	09+12+12+18	1.87	2.52	2.52	3.60		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	1.98	2.66	2.66	3.80		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	12+12+12+12	2.63	2.63	2.63	2.63		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	2.78	2.78	2.78	2.78		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)
	12+12+12+18	2.37	2.37	2.37	3.39		10.5 (2.6-11)	2950 (580-4000)	3.56	12.9 (2.5-17.5)	2.51	2.51	2.51	3.58		11.1 (2.2-12)	2750 (560-3900)	4.04	12 (2.4-17)

* A single indoor unit cannot be connected to the multi head outdoor unit as one by one system

AMW5-125U4RTAG

Model	Combination of Indoor Units	Cooling Capacity								Heating Capacity							
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER W/W	Total current (A) Rated (Min._Max.)	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP W/W	Total current (A) Rated (Min._Max.)
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
AMW5-125U4RTAG*	7	2.10					2.1 (0.8-2.8)	650 (180-1000)	3.2	2.9 (0.8-4.5)	2.50					2.5 (1-3.2)	750 (200-950)	3.3	3.3 (0.9-4.1)
	9	2.60					2.6 (0.8-3.2)	860 (220-1200)	3.0	3.9 (1-5.4)	3.00					3 (1-4)	930 (220-1250)	3.2	4 (1-5.4)
	12	3.50					3.5 (1.2-3.7)	1220 (220-1500)	2.9	5.5 (1-6.8)	3.90					3.9 (1-4.5)	1320 (220-1500)	3.0	5.7 (1-6.5)
	18	5.00					5 (1.6-6)	1650 (450-2200)	3.0	7.5 (2-10)	5.40					5.4 (1.75-6.7)	1800 (400-2200)	3.0	7.8 (1.7-9.6)
	24	7.00					7 (2.2-7.9)	2520 (450-3200)	2.8	11 (2-14.5)	7.50					7.5 (2.1-8)	2600 (450-3600)	2.9	11.3 (2-15.7)
	07+18	2.10	5.00				7.1 (2.4-8)	2100 (500-3300)	3.4	9.1 (2.3-14.9)	2.60	5.50				8.1 (2-8.5)	2300 (400-3400)	3.5	10 (1.7-14.8)
	07+24	1.80	6.20				8 (2.4-8)	2100 (500-3300)	3.8	9.1 (2.3-14.9)	2.00	7.00				9 (2-8.5)	2300 (400-3400)	3.9	10 (1.7-14.8)
	09+18	2.60	5.00				7.6 (2.4-9)	2200 (500-3500)	3.5	9.6 (2.3-15.9)	3.00	5.40				8.4 (2-9.5)	2350 (400-3600)	3.6	10.2 (1.7-15.7)
	09+24	2.50	7.00				9.5 (2.2-9.5)	2600 (500-3500)	3.7	11.3 (2.3-15.9)	3.00	7.50				10.5 (1.8-9.7)	2600 (400-3800)	4.0	11.3 (1.7-16.5)
	12+18	3.50	5.00				8.5 (2.2-9.5)	2600 (500-3500)	3.3	11.3 (2.3-15.9)	3.70	5.80				9.5 (1.8-9.7)	2600 (400-3800)	3.7	11.3 (1.7-16.5)
	12+24	3.30	6.70				10 (2.2-9.5)	2600 (500-3500)	3.8	11.3 (2.3-15.9)	3.80	7.20				11 (1.8-9.7)	2600 (400-3800)	4.2	11.3 (1.7-16.5)
	18+18	5.00	5.00				10 (2.2-10.5)	3000 (500-3850)	3.3	13 (2.3-17.4)	5.50	5.50				11 (1.8-11)	2650 (400-4000)	4.2	11.5 (1.7-17.4)
	18+24	5.00	7.00				12 (3-12.6)	3600 (828-5472)	3.3	15.6 (3.8-24.8)	5.50	7.50				13 (3-13.52)	3300 (567.6-4356)	3.9	14.5 (2.5-18.9)
	24+24	6.25	6.25				12.5 (3-13.13)	3600 (828-5472)	3.5	15.6 (3.8-24.8)	6.75	6.75				13.5 (3-14.04)	3300 (567.6-4356)	4.1	14.5 (2.5-18.9)
	07+07+18	2.00	2.00	5.00			9 (3-9.45)	2400 (552-3648)	3.8	10.4 (2.5-16.5)	2.50	2.50	5.50			10.5 (3-10.92)	2400 (412.8-3168)	4.4	10.6 (1.8-13.8)
	07+07+24	2.00	2.00	7.00			11 (3-11.55)	2400 (552-3648)	4.6	10.4 (2.5-16.5)	2.50	2.50	7.50			12.5 (3-13)	2400 (412.8-3168)	5.2	10.6 (1.8-13.8)
	07+09+18	2.00	2.60	5.00			9.6 (3-10.08)	2400 (552-3648)	4.0	10.4 (2.5-16.5)	2.50	3.00	5.50			11 (3-11.44)	2400 (412.8-3168)	4.6	10.6 (1.8-13.8)
	07+09+24	2.00	2.60	7.00			11.6 (3-12.18)	2400 (552-3648)	4.8	10.4 (2.5-16.5)	2.50	3.00	7.50			13 (3-13.52)	2400 (412.8-3168)	5.4	10.6 (1.8-13.8)
	07+12+18	2.00	3.50	5.00			10.5 (3-11.03)	2400 (552-3648)	4.4	10.4 (2.5-16.5)	2.50	4.00	5.50			12 (3-12.48)	2400 (412.8-3168)	5.0	10.6 (1.8-13.8)
	07+12+24	2.00	3.50	7.00			12.5 (3-13.13)	2400 (552-3648)	5.2	10.4 (2.5-16.5)	2.50	4.00	7.00			13.5 (3-14.04)	2400 (412.8-3168)	5.6	10.6 (1.8-13.8)
	07+18+18	2.00	5.00	5.00			12 (3-12.6)	2400 (552-3648)	5.0	10.4 (2.5-16.5)	2.50	5.50	5.50			13.5 (3-14.04)	2400 (412.8-3168)	5.6	10.6 (1.8-13.8)
	07+18+24	1.80	4.50	6.20			12.5 (3-13.13)	2400 (552-3648)	5.2	10.4 (2.5-16.5)	2.50	4.50	6.50			13.5 (3-14.04)	2400 (412.8-3168)	5.6	10.6 (1.8-13.8)
	07+24+24	1.50	5.50	5.50			12.5 (3-13.13)	2400 (552-3648)	5.2	10.4 (2.5-16.5)	1.90	5.80	5.80			13.5 (3-14.04)	2400 (412.8-3168)	5.6	10.6 (1.8-13.8)
	09+09+18	2.60	2.60	5.20			10.4 (3.4-10.92)	2400 (552-3648)	4.3	10.4 (2.5-16.5)	3.00	3.00	5.50			11.5 (3-11.96)	2400 (412.8-3168)	4.8	10.6 (1.8-13.8)
	09+09+24	2.60	2.60	7.00			12.2 (3.4-12.81)	2500 (575-3800)	4.9	10.8 (2.6-17.2)	3.00	3.00	7.50			13.5 (3-14.04)	2500 (430-3300)	5.4	11 (1.9-14.3)
	09+12+12	2.60	3.50	3.50			9.6 (3.4-10.08)	2500 (575-3800)	3.8	10.8 (2.6-17.2)	3.00	4.00	4.00			11 (3-11.44)	2500 (430-3300)	4.4	11 (1.9-14.3)
	09+12+18	2.60	3.50	5.20			11.3 (3.4-11.87)	2500 (575-3800)	4.5	10.8 (2.6-17.2)	3.00	4.00	5.50			12.5 (3-13)	2500 (430-3300)	5.0	11 (1.9-14.3)
	09+12+24	2.50	3.50	6.50			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	3.00	3.50	7.00			13.5 (3-14.04)	2500 (430-3300)	5.4	11 (1.9-14.3)
	09+18+18	2.60	4.90	5.00			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	3.00	5.25	5.25			13.5 (3-14.04)	2500 (430-3300)	5.4	11 (1.9-14.3)
	09+18+24	2.30	4.20	6.00			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	2.50	4.50	6.50			13.5 (3-14.04)	2500 (430-3300)	5.4	11 (1.9-14.3)
	09+24+24	1.70	5.40	5.40			12.5 (3-13.13)	2400 (552-3648)	5.2	10.4 (2.5-16.5)	2.10	5.70	5.70			13.5 (3-14.04)	2400 (412.8-3168)	5.6	10.6 (1.8-13.8)
	12+12+12	3.50	3.50	3.50			10.5 (3.4-11.03)	2500 (575-3800)	4.2	10.8 (2.6-17.2)	4.00	4.00	4.00			12 (3-12.48)	2500 (430-3300)	4.8	11 (1.9-14.3)
	12+12+18	3.50	3.50	5.00			12 (3.4-12.6)	2500 (575-3800)	4.8	10.8 (2.6-17.2)	3.60	3.60	5.00			12.2 (3-12.69)	2700 (464.4-3564)	4.5	11.9 (2-15.5)
	12+12+24	3.00	3.00	6.50			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	3.40	3.60	6.50			13.5 (3-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	12+18+18	3.10	4.70	4.70			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	3.50	5.00	5.00			13.5 (3-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	12+18+24	3.00	4.00	5.50			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	3.30	4.20	6.00			13.5 (3-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	12+24+24	2.50	5.00	5.00			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	2.70	5.40	5.40			13.5 (3-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	18+18+18	4.20	4.20	4.10			12.5 (3.4-13.13)	2500 (575-3800)	5.0	10.8 (2.6-17.2)	4.50	4.50	4.50			13.5 (3-14.04)	2800 (481.6-3696)	4.8	12.3 (2.1-16.1)
	07+07+07+07	2.00	2.00	2.00	2.00		8 (3-8.4)	2000 (460-3040)	4.0	8.6 (2.1-13.8)	2.50	2.50	2.50	2.50		10 (3.5-10.4)	2500 (430-3300)	4.0	11 (1.9-14.3)
	07+07+07+09	2.00	2.00	2.00	2.50		8.5 (3-8.93)	2100 (483-3192)	4.0	9.1 (2.2-14.5)	2.50	2.50	2.50	3.00		10.5 (3.5-10.92)	2600 (447.2-3432)	4.0	11.5 (1.9-14.9)
	07+07+07+12	2.00	2.00	2.00	3.50		9.5 (3-9.98)	2200 (506-3344)	4.3	9.5 (2.3-15.1)	2.50	2.50	2.50	4.00		11.5 (3.5-11.96)	2650 (455.8-3498)	4.3	11.7 (2-15.2)
	07+07+07+18	2.00	2.00	2.00	5.00		11 (3-11.55)	2300 (529-3496)	4.8	9.9 (2.4-15.8)	2.50	2.50	2.50	6.00		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)

Hisense Air Conditioning | Better Air

AMW5-125U4RTAG

Model	Combination of Indoor Units	Cooling Capacity								Heating Capacity							
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER W/W	Total current (A) Rated (Min._Max.)	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP W/W	Total current (A) Rated (Min._Max.)
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
AMW5-125U4RTAG*	07+07+07+24	2.00	2.00	2.00	6.50		12.5 (3-13.13)	2400 (552-3648)	5.2	10.4 (2.5-16.5)	2.00	2.00	2.00	7.50		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+07+09+09	2.00	2.00	2.50	2.50		9 (3-9.45)	2200 (506-3344)	4.1	9.5 (2.3-15.1)	2.50	2.50	3.50	3.50		12 (3.5-12.48)	2200 (378.4-2904)	5.5	9.7 (1.6-12.6)
	07+07+09+12	2.00	2.00	2.50	3.50		10 (3-10.5)	2300 (529-3496)	4.3	9.9 (2.4-15.8)	2.50	2.50	3.00	4.00		12 (3.5-12.48)	2200 (378.4-2904)	5.5	9.7 (1.6-12.6)
	07+07+09+18	2.00	2.00	3.50	5.00		12.5 (3-13.13)	2400 (552-3648)	5.2	10.4 (2.5-16.5)	2.00	2.00	4.00	5.50		13.5 (3.5-14.04)	2400 (412.8-3168)	5.6	10.6 (1.8-13.8)
	07+07+09+24	2.00	2.00	2.50	6.00		12.5 (3-13.13)	2400 (552-3648)	5.2	10.4 (2.5-16.5)	2.00	2.00	3.50	6.00		13.5 (3.5-14.04)	2500 (430-3300)	5.4	11 (1.9-14.3)
	07+07+12+12	2.00	2.00	3.50	3.50		11 (3-11.55)	2300 (529-3496)	4.8	9.9 (2.4-15.8)	2.50	2.50	4.00	4.00		13 (3.5-13.52)	2400 (412.8-3168)	5.4	10.6 (1.8-13.8)
	07+07+12+18	2.00	2.00	2.50	5.00		11.5 (3-12.08)	2400 (552-3648)	4.8	10.4 (2.5-16.5)	2.50	2.50	3.50	5.00		13.5 (3.5-14.04)	2500 (430-3300)	5.4	11 (1.9-14.3)
	07+07+12+24	2.00	2.00	3.00	5.50		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.00	2.00	3.50	6.00		13.5 (3.5-14.04)	2600 (447.2-3432)	5.2	11.5 (1.9-14.9)
	07+07+18+18	2.00	2.00	4.25	4.25		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.00	2.00	4.75	4.75		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+07+18+24	1.50	1.50	3.85	5.65		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.00	2.00	3.50	6.00		13.5 (3.5-14.04)	2750 (473-3630)	4.9	12.1 (2.1-15.8)
	07+07+24+24	1.35	1.35	4.90	4.90		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	1.65	1.65	5.10	5.10		13.5 (3.5-14.04)	2850 (490.2-3762)	4.7	12.6 (2.1-16.4)
	07+09+09+09	2.00	2.50	2.50	2.50		9.5 (3-9.98)	2700 (621-4104)	3.5	11.7 (2.8-18.6)	2.50	3.00	3.00	3.00		11.5 (3.5-11.96)	2400 (412.8-3168)	4.8	10.6 (1.8-13.8)
	07+09+09+12	2.00	2.50	2.50	3.50		10.5 (3-11.03)	2700 (621-4104)	3.9	11.7 (2.8-18.6)	2.50	3.00	3.00	4.00		12.5 (3.5-13)	2500 (430-3300)	5.0	11 (1.9-14.3)
	07+09+09+18	2.00	2.50	2.50	5.00		12 (3-12.6)	2700 (621-4104)	4.4	11.7 (2.8-18.6)	2.50	3.00	3.00	5.00		13.5 (3.5-14.04)	2600 (447.2-3432)	5.2	11.5 (1.9-14.9)
	07+09+09+24	1.90	2.30	2.30	6.00		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.00	2.50	2.50	6.50		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+09+12+18	1.90	2.30	3.40	4.90		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.10	2.60	3.50	5.30		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+09+12+24	1.70	2.10	2.90	5.80		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.00	2.40	3.10	6.00		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+09+18+18	1.80	2.10	4.30	4.30		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	1.90	2.40	4.60	4.60		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+09+18+24	1.50	1.90	3.80	5.30		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	1.80	2.20	4.00	5.50		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+09+24+24	1.35	1.35	4.90	4.90		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	1.75	1.75	5.00	5.00		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+12+12+12	2.00	3.50	3.50	3.50		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.00	3.50	3.50	3.50		12.5 (3.5-13)	2400 (412.8-3168)	5.2	10.6 (1.8-13.8)
	07+12+12+18	2.00	3.00	3.00	4.50		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	2.00	3.50	3.50	4.50		13.5 (3.5-14.04)	2600 (447.2-3432)	5.2	11.5 (1.9-14.9)
	07+12+12+24	1.50	2.50	2.50	6.00		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	1.80	3.00	3.00	5.70		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+12+18+18	1.70	2.80	4.00	4.00		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	1.80	2.90	4.40	4.40		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	07+12+18+24	1.40	2.50	3.50	5.10		12.5 (3-13.13)	2700 (621-4104)	4.6	11.7 (2.8-18.6)	1.60	2.50	4.10	5.30		13.5 (3.5-14.04)	2700 (464.4-3564)	5.0	11.9 (2-15.5)
	09+09+09+09	2.60	2.60	2.60	2.60		10.4 (3.4-10.92)	2700 (621-4104)	3.9	11.7 (2.8-18.6)	3.00	3.00	3.00	3.00		12 (3.5-12.48)	2850 (490.2-3762)	4.2	12.6 (2.1-16.4)
	09+09+09+12	2.60	2.60	2.60	3.50		11.3 (3.4-11.87)	2750 (632.5-4180)	4.1	11.9 (2.9-18.9)	3.00	3.00	3.00	4.00		13 (3.5-13.52)	2900 (498.8-3828)	4.5	12.8 (2.2-16.6)
	09+09+09+18	2.50	2.50	2.50	5.00		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.50	2.50	2.50	6.00		13.5 (3.5-14.04)	3000 (516-3960)	4.5	13.2 (2.2-17.2)
	09+09+09+24	2.00	2.00	2.00	6.50		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.30	2.30	2.30	6.50		13.4 (3.5-13.94)	3200 (550.4-4224)	4.2	14.1 (2.4-18.4)
	09+09+12+12	2.50	2.50	3.50	3.50		12 (3.4-12.6)	2800 (644-4256)	4.3	12.1 (2.9-19.3)	3.00	3.00	3.75	3.75		13.5 (3.5-14.04)	2950 (507.4-3841)	4.6	13 (2.2-16.7)
	09+09+12+18	2.50	2.50	3.20	4.30		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.50	2.50	3.50	5.00		13.5 (3.5-14.04)	2950 (507.4-3894)	4.6	13 (2.2-16.9)
	09+09+12+24	2.00	2.00	3.00	5.50		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.00	2.00	3.50	6.00		13.5 (3.5-14.04)	2950 (507.4-3894)	4.6	13 (2.2-16.9)
	09+09+18+18	2.00	2.00	4.25	4.25		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.00	2.00	4.75	4.75		13.5 (3.5-14.04)	2900 (498.8-3828)	4.7	12.8 (2.2-16.6)
	09+09+18+24	1.90	1.90	3.70	5.00		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	1.80	1.80	4.50	5.40		13.5 (3.5-14.04)	2900 (498.8-3828)	4.7	12.8 (2.2-16.6)
	09+12+12+12	2.30	3.40	3.40	3.40		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.40	3.70	3.70	3.70		13.5 (3.5-14.04)	2950 (507.4-4078)	4.6	13 (2.2-17.7)
	09+12+12+18	2.20	3.00	3.00	4.30		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.50	3.20	3.20	4.60		13.5 (3.5-14.04)	2950 (507.4-3894)	4.6	13 (2.2-16.9)
	09+12+12+24	1.90	2.40	2.40	5.80		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.00	3.00	3.00	5.50		13.5 (3.5-14.04)	2950 (507.4-3894)	4.6	13 (2.2-16.9)
	09+12+18+18	1.60	2.90	4.00	4.00		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	1.80	2.90	4.40	4.40		13.5 (3.5-14.04)	2950 (507.4-3894)	4.6	13 (2.2-16.9)
	12+12+12+12	3.10	3.10	3.10	3.20		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	3.40	3.40	3.40	3.30		13.5 (3.5-14.04)	2950 (507.4-4105)	4.6	13 (2.2-17.8)
	12+12+12+18	2.70	2.70	2.70	4.40		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	3.00	3.00	3.00	4.50		13.5 (3.5-14.04)	2950 (507.4-3894)	4.6	13 (2.2-16.9)
	12+12+18+18	1.35	1.35	4.90	4.90		12.5 (3.4-13.13)	2800 (644-4256)	4.5	12.1 (2.9-19.3)	2.85	2.85	3.90	3.90		13.5 (3.5-14.04)	2950 (507.4-3894)	4.6	13 (2.2-16.9)
	07+07+07+07+18	1.93	1.93	1.93	1.93	4.78	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.17	2.17	2.17	2.17	4.82	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+07+07+24	1.65	1.65	1.65	1.65	5.90	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	1.92	1.92	1.92	1.92	5.82	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+07+09+18	1.85	1.85	1.85	2.31	4.64	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.11	2.11	2.11	2.54	4.68	13.55 (3.6-14.09)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+07+09+24	1.61	1.61	1.61	2.02	5.65	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	1.88	1.88	1.88	2.26	5.61	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+07+12+18	1.72	1.72	1.72	3.00	4.34	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	1.98	1.98	1.98	3.17	4.39	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+07+12+24	1.52	1.52	1.52	2.65	5.31	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	1.77	1.77	1.77	2.84	5.35	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+07+18+18	1.50	1.50	1.50	4.00	4.00	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.60	1.60	1.60	4.35	4.35	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+07+18+24	1.30	1.30	1.30	3.60	5.00	12.5 (3.5-13.13)	3800 (874-6650)	3.3	16.4 (4-30.1)	1.50	1.50	1.50	3.90	5.10	13.5 (3.6-14.04)	3950 (679.4-6600)	3.4	17.4 (3-28.7)
	07+07+09+09+18	1.78	1.78	2.23	2.23	4.48	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.05	2.05	2.46	2.46	4.48	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+09+09+24	1.56	1.56	1.95	1.95	5.48	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	1.83	1.83	2.19	2.19	5.47	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+09+12+18	1.67	1.67	2.08	2.91	4.17	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	1.92	1.92	2.30	3.07	4.29	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+09+12+24	1.84	1.84	2.57	2.57	3.68	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	2.08	2.08	2.78	2.78	3.78	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+09+18+18	1.50	1.50	1.70	3.90	3.90	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	1.60	1.60	1.80	4.25	4.25	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+07+09+18+24	1.35	1.35	1.70	3.38	4.72	12.5 (3.5-13.13)	3800 (874-6650)	3.3	16.4 (4-30.1)	1.60	1.60	1.90	3.50	4.90	13.5 (3.6-14.04)	3950 (679.4-6600)	3.4	17.4 (3-28.7)
	07+07+12+18+18	1.43	1.43	2.50	3.57	3.57	12.5 (3.5-13.13)	3800 (874-6650)	3.3	16.4 (4-30.1)	1.70	1.70	2.70	3.70	3.70	13.5 (3.6-14.04)	3950 (679.4-6600)	3.4	17.4 (3-28.7)
	07+07+12+18+24	1.28	1.28	2.24	3.20	4.50	12.5 (3.5-13.13)	3800 (874-6650)	3.3	16.4 (4-30.1)	1.53	1.53	2.45	3.39	4.60	13.5 (3.6-14.04)	3950 (679.4-6600)	3.4	17.4 (3-28.7)
	07+09+09+09+18	1.61	2.02	2.02	2.82	4.03	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.88	2.25	2.25	3.00	4.12	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+09+09+09+24	1.50	1.90	1.90	1.90	5.30	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.77	2.10	2.10	2.10	5.43	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+09+09+12+18	1.61	2.02	2.02	2.82	4.03	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.88	2.25	2.25	3.00	4.12	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)

Hisense Air Conditioning | Better Air

AMW5-125U4RTAG

Model	Combination of Indoor Units	Cooling Capacity									Heating Capacity								
		Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	EER W/W	Total current (A) Rated (Min._Max.)	Capacity of each indoor unit (kW)					Total capacity (kW) Rated (Min._Max.)	Total power input (W) Rated (Min._Max.)	COP W/W	Total current (A) Rated (Min._Max.)
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
AMW5-125U4RTAG*	07+09+09+12+24	1.44	1.78	1.78	2.50	5.00	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.69	2.03	2.03	2.70	5.05	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+09+12+12+18	1.50	1.90	2.60	2.60	3.90	12.5 (3.5-13.13)	3800 (874-6650)	3.3	16.4 (4-30.1)	1.65	1.95	2.70	3.60	3.60	13.5 (3.6-14.04)	3950 (679.4-6600)	3.4	17.4 (3-28.7)
	07+09+12+12+24	1.44	1.78	1.78	2.50	5.00	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.69	2.03	2.03	2.70	5.05	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+09+12+18+18	1.39	1.74	2.43	3.47	3.47	12.5 (3.5-13.13)	3800 (874-6650)	3.3	16.4 (4-30.1)	1.65	1.95	2.70	3.60	3.60	13.5 (3.6-14.04)	3950 (679.4-6600)	3.4	17.4 (3-28.7)
	07+09+09+12+18	1.40	1.75	1.75	3.80	3.80	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.70	2.00	2.80	2.80	4.20	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+09+09+18+18	1.40	1.75	1.75	3.80	3.80	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.50	1.90	1.90	4.10	4.10	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	07+12+12+12+18	1.40	2.50	2.50	2.50	3.60	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.60	2.60	2.60	2.60	4.10	13.5 (3.6-14.04)	3950 (679.4-6400)	3	17.4 (3-27.8)
	09+09+09+09+09	2.50	2.50	2.50	2.50	2.50	12.5 (3.5-12.3)	3610 (830.3-6500)	3.5	15.6 (3.8-29.4)	2.70	2.70	2.70	2.70	2.70	13.5 (3.6-14.04)	3600 (650-5832)	3.8	15.9 (2.8-25.4)
	09+09+09+09+12	2.30	2.30	2.30	2.30	3.30	12.5 (3.5-13.13)	3700 (851-6500)	3.4	16 (3.9-29.4)	2.50	2.50	2.50	2.50	3.50	13.5 (3.6-14.04)	3650 (627.8-5913)	3.7	16.1 (2.7-25.7)
	09+09+09+09+18	2.00	2.00	2.00	2.00	4.50	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.30	2.30	2.30	2.30	4.30	13.5 (3.6-14.04)	3950 (679.4-6399)	3.4	17.4 (3-27.8)
	09+09+09+09+24	1.83	1.83	1.83	1.83	5.18	12.5 (3.5-13.13)	3700 (851-6500)	3.4	16 (3.9-29.4)	2.08	2.08	2.08	2.08	5.20	13.5 (3.6-14.04)	3850 (662.2-6237)	3.5	17 (2.9-27.1)
	09+09+09+12+12	2.00	2.00	2.00	3.25	3.25	12.5 (3.5-13.13)	3750 (862.5-6500)	3.3	16.2 (3.9-29.4)	2.30	2.30	2.30	3.30	3.30	13.5 (3.6-14.04)	3900 (670.8-6318)	3.5	17.2 (2.9-27.5)
	09+09+09+12+18	1.95	1.95	1.95	2.73	3.92	12.5 (3.5-13.13)	3700 (851-6500)	3.4	16 (3.9-29.4)	2.19	2.19	2.19	2.92	4.01	13.5 (3.6-14.04)	3850 (662.2-6237)	3.5	17 (2.9-27.1)
	09+09+09+12+24	1.74	1.74	1.74	2.43	4.85	12.5 (3.5-13.13)	3700 (851-6500)	3.4	16 (3.9-29.4)	1.97	1.97	1.97	2.63	4.96	13.5 (3.6-14.04)	3850 (662.2-6237)	3.5	17 (2.9-27.1)
	09+09+09+18+18	1.70	1.70	1.70	3.70	3.70	12.5 (3.5-13.13)	3800 (874-6600)	3.3	16.4 (4-29.9)	1.80	1.80	1.80	4.05	4.05	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	09+09+12+12+12	2.05	2.05	2.80	2.80	2.80	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.10	2.10	3.10	3.10	3.10	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	09+09+12+12+18	1.84	1.84	2.57	2.57	3.68	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.08	2.08	2.78	2.78	3.78	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	09+12+12+12+12	1.84	1.84	2.57	2.57	3.68	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.08	2.08	2.78	2.78	3.78	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	09+12+12+12+18	1.70	2.40	2.40	2.40	3.60	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-29.4)	2.00	2.50	2.50	2.50	4.00	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)
	12+12+12+12+12	2.50	2.50	2.50	2.50	2.50	12.5 (3.5-13.13)	3800 (874-6500)	3.3	16.4 (4-2500)	2.00	2.50	2.50	2.50	4.00	13.5 (3.6-14.04)	3950 (679.4-6400)	3.4	17.4 (3-27.8)

* A single indoor unit cannot be connected to the multi head outdoor unit as one by one system.

Hisense Australia Pty Ltd.
ABN 55105022080
Level 1/37 Dalmore Dr, Scoresby VIC 3179
hisense.com.au

Customer Support
Email: hvacorders@hisense.com
Phone: 1800 447 367

Note: Product design and specifications subject to change without prior notice.
© 2026 Hisense Corporation. All rights reserved. Hisense the Hisense logo and the Just Makes Sense logo are trademarks or registered trademarks of Hisense Group in China and/or other countries. All rights reserved. All other company names, brand names, trademarks and logos are the property of their respective owners. All rights reserved.

Ver. 22042026